



PACIFIC CYLINDROL

CYLINDER OIL-460 & 680

Introduction : PACIFIC CYLINDROL OIL is straight cylinder oils manufactured from premium performance cylinder oil base stock & additives to work at high temperatures. These oils have good film strength and thermal degradation characteristic

Application :

1. Recommended for lubrication of cylinders of steam engines & steam condensers.
2. Ideal products for lubrication of heavily loaded slow speed worm gears.
3. Recommended for lubrication of paper and textile mill calendar bearings and sugar mill roller bearings.

Performance Benefits :

1. Enables higher loading of equipment due to its high load carrying ability
2. Reduces wear of cylinder walls and piston rings
3. Good corrosion and rust protection
4. Reduces deposit formation at high temperatures
5. Excellent adhesive property, which helps to resist water washing

Specifications : BIS 2297 - 1997

Characteristics

	PACIFIC CYLINDROL	
ISO VG	460	680
KINEMATIC VISCOSITY @ 40°C, cst	420-480	640-680
@ 100°C, cSt	28-32	34-38
VISCOSITY INDEX, MIN	90	85
POUR POINT, °C, MAX	-6	-0
FLASH POINT, COC °C, MIN	280	280
CCR % WT. (TYPICAL)	2.5	3.5

Pack Size : 210 Ltrs. & 20 Ltrs.

*These Specifications are of a Particular Lot they can differ from lot to lot but will not effect the performance of the oil