



Pacific Product Data Sheet

PACIFIC GEL GREASE

Introduction : Pacific Gel Grease is prepared from high performance base oils, special lithium semi-complex thickener and additives to improve high thermal stability to ensure prolonged resistance to the effects of heavy breaking. Its molecular structure provides product stability under wide variation of working temperature.

Application :

1. Wheel Bearings of all types of cars, buses, trucks, highway equipment and farm equipment.
2. Chassis of all Automobiles.

Performance Benefits :

1. Long drain period.
2. High thermal stability.
3. Protection to wear & corrosion.
4. Good adhesive property.
5. Increases bearing life.
6. Good water washout resistance.
7. High drop point.

Specifications : NLGI- 2.5

Characteristic

1. Appearance	Transparent Red
2. Consistency of worked grease, @ 25+0.5oC, 0.1mm units (60 double strokes)	250-265
3. Base oil Viscosity @100oC cSt min.	10.5
4. Drop Point oC min.	240
5. Soap Type	Lithium Semi- complex
6. Structure	Smooth & Buttery
7. Four Ball Weld Point kgf, min.	250

Pack Size : 180 Kg, 5 Kg, 2 Kg, 1 Kg, 500 gm

Contact our Toll Free No. **18002122411**

*These Specifications are of a Particular Lot they can differ from lot to lot but will not effect the performance of the oil